

TechStar standard production list

Size Inch	Manufacturer Part-no	Dot Format	A.A. (mm)	Outline Size (mm)	Contrast (Cr)	Backlight	Brightness	Top. (°C)	Tstor. (°C)	Interface	Panel	Controller	Colors	Touch Panel	view angle	commons	comments
1.77	TSM-T177MTHS-02	128xRGBx160	28.03*35.04	34.70x46.7x2.5	250	2LED	320	-20-70	-30-80	8bits parallel	TM	ST7735S	262K	-	12:00		20pin 0.5mm
1.77	TSM-T177MZHS-03	128xRGBx160	28.03x35.04	34.70x46.7x2.5	250	2LED	320	-20-70	-30-80	4lines serials interface	CPT	ST7735S	262K	-	12:00		20pin 0.5mm
2.00	TSM-T200MHFI-01	176xRGBx220	31.68x39.60	37.68X51.30X2.23	250	3LED	180	-20-70	-30-80	8bits parallel	HSD	ILI9225G	262K	-	12:00		20pin soldering
2.36	TSM-T236MZQO-01	480xRGBx234	48x35.69	55.2x44.75x2.9	250	2LED	250	-20-70	-30-80	8bits RGB	CPT	OTA5182A	262K		6:00	car black box	40pin,connector
2.40	TSM-T240MCQI-01	240xRGBx320	36.72x48.96	42.72x60.26x2.46	250	4LED	200	-20-70	-30-80	8bits80 parallel	CMO	ILI9341V	262k		12:00		37pin soldering
2.40	TSM-T240MCQI-01P	240xRGBx320	36.72x48.96	42.72x60.26x3.7	250	4LED	160	-20-70	-30-80	8bits80 parallel	CMO	ILI9341V	262k		12:00		37pin soldering
2.70	TSM-T270MZQI-04	240xRGBx320	40.50x54.00	45.70x62.60x2.45	400	4LED	350	-20-70	-30-80	8bits RGB interface	CPT	ILI9341V	262k		3:00		40pins connector
2.83	TSM-T280MTQI-03	240xRGBx320	43.2X57.6	50X69.2X2.4	500	4LED	220	-20-70	-30-80	8/16bits parallel	TM	ILI9341V	262k		6:00		37pin,soldering type
2.83	TSM-T280MTQI-03P	240xRGBx320	43.2X57.6	50X69.2X3.65	500	4LED	200	-20-70	-30-80	8/16bits parallel	TM	ILI9341V	262k	with TP	6:00	without icon	37pin,soldering type
2.83	TSM-T280MTQI-04P	240xRGBx320	43.2X57.6	50X69.2X3.65	500	4LED	200	-20-70	-30-80	8/16bits parallel	TM	ILI9341V	262k	with TP	6:00	with icon based on -03	37pin,soldering type
3.50	TSM-T350MTHH-01P	320xRGBx480	48.96X73.14	54.66x82.94x3.45	800	6LED	290	-20-70	-30-80	18bits RGB+SPI	TM	HX8357D	262k	with TP	ALL		45pin,connector type
3.50	TSM-T350MTQI-01	240xRGBx320	71.52x53.64	85x64x2.93	150	6LED	100	-20-70	-30-80	RGB 6bit+SPI	TM	ILI9341V	262K		6:00	Transflective	50pin connector
3.50	TSM-T350MHHH-05	320xRGBx480	48.96X73.44	54.66X82.9X2.1	500	6LED	380	-20-70	-30-80	18bits RGB+SPI	HSD	HX8357D	262K		12:00		45pin,connector type
3.50	TSM-T350MHHH-05P	320xRGBx480	48.96X73.44	54.66X82.9X3.45	500	6LED	300	-20-70	-30-80	18bits RGB+SPI	HSD	HX8357D	262K	with TP	12:00		45pin,connector type
3.50	TSM-T350MCQH-05	240xRGBx320	70.08X52.56	76.9X63.9X3.2	400	6LED	300	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m		12:00		54pins connector
3.50	TSM-T350MCQH-05P	240xRGBx320	70.08X52.56	76.9X63.9X4.25	400	6LED	240	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m	with TP	12:00	add TP based on -05	54pins connector
3.50	TSM-T350MCQH-05C	240xRGBx320	70.08X52.56	76.9X63.9X4.37	400	6LED	250	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m	with CTP	12:00		54pins connector
3.50	TSM-T350MCQH-11	240xRGBx320	70.08X52.56	76.9X63.9X3.2	400	6LED	300	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m		12:00		54pins connector
3.50	TSM-T350MCQH-11P	240xRGBx320	70.08X52.56	76.9X63.9X4.25	400	6LED	240	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m	with TP	12:00		54pins connector
3.50	TSM-T350MCQH-18	240xRGBx320	70.08X52.56	76.9X63.9X3.3	400	6LED	400	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m		12:00	无铁框	54pins connector
3.50	TSM-T350MCQH-18P	240xRGBx320	70.08X52.56	76.9X63.9X4.4	400	6LED	320	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m	with TP	12:00	无铁框	54pins connector
3.50	TSM-T350MCQH-23	240xRGBx320	70.08X52.56	76.9X63.9X3.2	400	6LED	700	-20-70	-30-80	24bits RGB	CMO	HX8238D	16.7m		12:00		54pins connector
3.50	TSM-T350MTQV-01	240xRGBx320	70.08X52.56	76.9X63.9X3.15	500	6LED	300	-20-70	-30-80	24bits RGB	TM	NV3035	16.7m		12:00		54pins connector
3.50	TSM-T350MTQV-01P	240xRGBx320	70.08X52.56	76.9X63.9X4.4	500	6LED	240	-20-70	-30-80	24bits RGB	TM	NV3035	16.7m	with TP	12:00		54pins connector
3.50	TSM-T350MTQV-07	240xRGBx320	70.08X52.56	76.9X63.9X4.15	500	6LED	300	-20-70	-30-80	24bits RGB	TM	NV3035	16.7m		12:00		54pins connector
3.50	TSM-T350MTQV-07P	240xRGBx320	70.08X52.56	76.9X63.9X4.4	500	6LED	240	-20-70	-30-80	24bits RGB	TM	NV3035	16.7m	with TP	12:00		54pins connector
3.50	TSM-T350MTQV-18	240xRGBx320	70.08X52.56	76.9X63.9X3.15	500	6LED	450	-20-70	-30-80	24bits RGB	TM	NV3035	16.7m		12:00		54pins connector
3.50	TSM-T350MLQZ-01	240xRGBx320	70.08X52.56	76.9X63.9X3.10	400	6LED	450	-20-70	-30-80	CPU&RGB&SPI	Laibao	SSD2119	262k		6:00		50pin connector
3.50	TSM-T350MLQZ-01P	240xRGBx320	70.08X52.56	76.9X63.9X3.10	400	6LED	360	-20-70	-30-80	CPU&RGB&SPI	Laibao	SSD2119	262k	with TP	6:00		50pin connector
3.50	TSM-T350MLQZ-02	240xRGBx320	70.08X52.56	76.9X63.9X3.10	400	6LED	450	-20-70	-30-80	CPU&RGB&SPI	Laibao	SSD2119	262k		6:00	长FPC	60pin connector
3.50	TSM-T350MLQZ-02P	240xRGBx320	70.08X52.56	76.9X63.9X4.30	400	6LED	360	-20-70	-30-80	CPU&RGB&SPI	Laibao	SSD2119	262k	with TP	6:00	长FPC	60pin connector
3.50	TSM-T350MLQZ-04	240xRGBx320	70.08X52.56	76.9X63.9X3.10	400	6LED	450	-20-70	-30-80	CPU&RGB&SPI		SSD2119	262k		6:00	Mono TFT	50pin connector
3.50	TSM-T350MPNO-01	480xRGBx272	77.76X43.52	86.8X56.5X2.75		6LED	350	-20-70	-30-80	24bits RGB	GP	OTA5180A	16.7m		6:00		40pin connector
3.50	TSM-T350MPNO-01P	480xRGBx272	77.76X43.52	86.8X56.5X3.9		6LED	280	-20-70	-30-80	24bits RGB	GP	OTA5180A	16.7m		6:00		40pin connector

